

CR

CRUSHER



- | | | | |
|--|---|--|--|
| 
PRIMARY
DEMOLITION | 
REINFORCED
CONCRETE | 
QUICK
MAINTENANCE | 
BIBOOSTER
TECHNOLOGY |
| 
REPLACEABLE
TEETH/BLADES | 
SPEED
VALVE | 
HYDRAULIC
ROTATION | 
SMART BOX |





The **specific tooth profile**, studied to remain sharp despite wear, maximizes penetration.




The **Speed-Valve** improves productivity and protects the hydraulic system from pressure peaks.




The **twin-pin system** enables a larger opening and higher power, even at maximum opening.



The **quick and easy routine maintenance** allows to reduce intervention times and costs.



4-sided usable cutting edges before replacement. **Interchangeable teeth.**



Real-time tracking of equipment performance.




The continuous **hydraulic rotation** enables precise positioning in high reach demolition and the double-row thrust bearing ensures high robustness and increases safety.



CR crusher can be equipped with **BIBOOSTER*** technology which multiplies the performance of the attachment, increasing the crushing force e the cycles per minute, with a sensible reduction of total weight and fuel consumption.

**check availability of models with the sales office*

MAXIMUM POWER FOR PRIMARY DEMOLITION



DATA SHEETS

MODEL		CR2	CR4	CR5	CR5R	CR15R	CR20R	CR26R	CR26BB	CR40R	CR60R	CR80R	CR100R	CR120R
ROTATION		Mechanical			360° Hydraulic									
EXCAVATOR WEIGHT	t	03-05	03-06	06-10	07-11	16-20	21-26	27-35	27-35	45-55	60-70	75-95	100-120	120-140
TOOL WEIGHT *	kg	240	320	530	690	1.600	2.200	2.900	2.700	4.820	6.700	8.650	11.600	12.000
OPENING	mm	360/0	440/25	450/0	450/0	800/0	1.050/0	1.100/0	1.100/0	1.350/0	1.580/0	1.800/0	2.050/0	2.310/320
HEIGHT	mm	1.070	1.070	1.290	1.315	1.800	2.030	2.200	2.200	2.800	3.020	3.400	3.200	3.300
HYDRAULIC WORKING PRESSURE	bar	180-220	250	200-250	200-250	320-350	320-350	320-350	280-320	320-350	320-350	320-350	320-350	320-350
OIL FLOW	l/min	30-50	65	50-90	50-90	130-150	180-220	220-250	220-250	250-300	500-600	500-600	600-800	600-800

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.
* Tool weight does include Mantovanibenne top bracket.